

Typing a tiltrotator (without serial number)

Latest update: 2018-08-08



Gen I

1. Ear diam. (axle), screw placement dir.	2. Piston diam.	3. Model of yoke	4. Axle diam.	Model
36mm (30mm), ↓	32mm		25mm (23,8mm)	EC02
60mm (40mm), ↓	32mm	Machined	30mm (28,8mm)	EC05
60mm (40mm), ↓	32mm	Casted	30mm (28,8mm)	EC05B
70mm (50mm), ↓	32mm	Machined	30mm (28,8mm)	EC10
70mm (50mm), ↓	32mm	Casted	35mm (32,7mm)	EC10B
70mm (55mm), ←	32mm	Machined	30mm (28,8mm)	EC15
70mm (55mm), ←	32mm	Casted	35mm (32,7mm)	EC15B
80mm (60mm), ↓	40mm	Machined	35mm (30,8mm)	EC20
80mm (60mm), ↓	40mm	Casted (with lubric.)	35mm (30,8mm)	EC20HD
80mm (60mm), ↓	40mm	Casted (lubric. free)	35mm (32,7mm)	EC20B
80mm (70mm), ↓	50mm	Machined	45mm (41,3mm)	EC30
80mm (70mm), ↓	45mm	Machined	45mm (41,3mm)	EC30

Gen II

1. Outer diam. of axle, (No. of bolts)	2. Piston diam.	5. No. of cylinders	Model
79mm (4 bolts)	25mm	1	EC204
90mm (4 bolts)	32mm	1	EC206
90mm (4 bolts)	32mm	2	EC209
110mm (7 bolts)	32mm	2	EC214
110mm (7 bolts)	45mm	2	EC219
127mm (9 bolts)	45mm	2	EC226
148mm (8 bolts)	45mm	2	EC233