

# Pallet fork

## Forklift frame for excavators



Engcon's pallet fork – A robust and cleverly engineered design for best visibility. Tempered forks guarantee a long service life.

**NOTE!** Always consult the applicable safety instructions for using the pallet fork on each individual machine. When using the pallet fork together with a tiltrotator, a load-holding valve must be fitted to the tiltrotator.

All Engcon tiltrotators are fitted with load-holding valves in the tilt cylinders as standard equipment.

- » The EC-Oil automatic quick hitch system connects the hydraulics without the operator needing to leave the cab.
- » Operation of hydraulic pallet forks is done from within the cab
- » Mechanical hydraulic pallet forks are held in the correct position with a robust latch and the position is adjusted manually.
- » Forged forks for maximum durability and service life

**GH** = Mechanical fork widening,

**GHH** = Hydraulic fork widening

**GHH1200L** = Hydraulic fork widening, Light version for lighter machines.



**NEW!** The EC-Oil automatic quick hitch system is a free standard on all engcon's hydraulic tools with S45-S80 attachment

## Specifications

Model	GH1000	GH1200	GHH1200	GHH1200L	GHH1200L
Width: (mm)	1 000	1 200	1 200	1 200	1 200
Blade: (mm)	100x40x1 200	125x45x1 200	125x45x1 200	100x40x1 200	125x45x1 200
Weight: (kg)*	180	360	400	260	313
TP500 (t)	2,9	4,7	4,7	2,9	4,7

\* Depending on bracket

## CHANGE THE WORLD OF DIGGING

engcon International | Box 111, SE-833 22 Strömsund, Sweden  
 Phone +46 670 178 00 | E-mail [international@engcon.com](mailto:international@engcon.com) | Web [engcon.com](http://engcon.com)