

# Finger grab

Our finger grab\* is the next level in handling brush, twigs and branches. With reinforced arms, it's built for demanding tasks.

Say goodbye to jamming problems – the finger grip opens smoothly every time so you can lift what you need without the problem of debris. And stay calm in the cab as the grapple comes with EC-Oil as standard.

## EC-Oil – the key to our system

It allows you to quickly change hydraulic attachments or disconnect the tiltrotator if you need more breakout force. And in seconds, and directly from the cab. The EC-Oil automatic oil coupling is now our standard.

\* In cooperation with Hultdins AB.



## Specifications

Model	FG12R	FG16R	FG20R
Weight (lbs)	694	1,045	1,234
Max load (lbs)	13,000	17,000	22,000
Grab area, tip–tip (ft²)	403	558	806
Max grab width, A (inch)	58.9	59.4	89.5
Min grab width, A (inch)	3.2	3.7	7
Max width, B (inch)	17.8	20.9	20.9
Quick hitch standard	S45	S60	S70
Base machine weight (lbs)	19,800	26,400	35,200
	-30,800	-39,600	-48,500
Prepared for EC-Oil	✓	✓	✓

**CHANGE THE WORLD OF DIGGING**

engcon Canada Inc | 3220 Av. Jacques-Bureau, Laval QC H7P 0A9

E-mail [canada@engcon.com](mailto:canada@engcon.com) | Web [engcon.com](http://engcon.com)