

PP3200

Compactor

engcon[®]

**For all excavators between 13 200–26 400 lbs
(6–12 metric ton)**



- » Easily adaptable for the EC-Oil automatic oil connector system and can thus be connected without the operator having to leave the cab.
- » Low flow requirement (9.25 gallons) allows the PP3200 to be run directly off the extra connections on the tiltrotator.
- » Variable working width.
- » Specially adapted compactor pads.
- » Compaction plate in hard-wearing steel.
- » Side plating for leveling-off filler material.
- » Open short ends to facilitate clearing the top of the plate.
- » Joined with rubber elements located for effective insulation of the vibrators combined with adequate stiffness for grading.
- » The vibrator unit and hydraulic parts are well-protected inside the side plates.
- » Can be fitted with optional bracket.
- » Complies with European safety standards.
- » Supplied as standard excluding bracket and machine hoses.



Accessories: Extension plates, trenching blade, specially adapted compactor pads for e.g. packing in sheet-pilings.

Specifications

Model	PP3200
Compaction force (lbs):	7,050
Compaction area: (inch ²)	15.7–22.0
Max hydraulic pressure: (psi)	3,200
Rec hydraulic flow: (gal/min)	9.0
Max continuous return line pressure: (psi)	145
Weight excluding attachment point: (lbs)	1,040
Length: (inch)	39.4
Width: (inch)	19.7–27.6
Height: (inch)	23.2

The EC-Oil automatic Quick Coupler system is a free standard on all engcon's hydraulic tools with S40–S80 attachment points.

CHANGE THE WORLD OF DIGGING

engcon Canada Inc | 3220 Av. Jacques-Bureau, Laval QC H7P 0A9

E-mail canada@engcon.com | Web engcon.com