

Detachable sweeper

For all excavators between 8,800-41,900 lbs (4-19 metric ton)

Sweeper – engcon's SWD detachable sweeper – can also be retrofitted.

Just like the GRD grabber cassette, the SWD sweeper can be retrofitted on the Q-Safe™ D quick coupler by fastening the single hook on the coupler's two suspension hooks and then locking the sweeper and connecting the hydraulics with a single hand maneuver – quick and easy. The SWD is operated by a heavy duty hydraulic motor and is raised or lowered by a hydraulic cylinder.

The SWD has a flexible design and can be adapted widthwise to precisely fit the job in hand – everything from cable sweeping to sweeping large areas that need cleaning. Reduces the need for manual labor and makes work safer. SWD Is available in several widths and can be used with engcon's new Q-Safe Detachable quick coupler.



Specifications

Model	SWD40	SWD45	SWD60
Length, cassette A: (inch)	17.7	23.1	26.2
Length, arm B: (inch)*	33.2	34.4	38.4
Width, cassette C: (inch)	12.3	14.3	16.7
Width, guard D: (inch)**	13.3/47.2	17.7/55.1	17.7/62.9
Height, guard E: (inch)	26	26	26
Max total length A+F (inch)*,**	60	67.3	78.7
Diameter, brush G: (inch)***	23.6/27.6	23.6/27.6	23.6/27.6/36
Width, brush H: (inch)	12.6/47.2	16.5/55.1	16.5/63
Maximum weight: (lbs)*,**	280	410	463
Oil flow min/max: (gal/min)	6/16	5/16	5/16
Fits couplers:	S40	S45	S60

* In the standard version

** Depends on sweeper brush

*** 36 inch can only be used with long arm (38.4 inch)

Included brushes:

SWD40: 12.6 inch, SWD45: 16.5 inch, SWD60: 16.5 inch.



CHANGE THE WORLD OF DIGGING