

PP3200

Compactor

engcon[®]

For all excavators in the 6–12 tonne weight classes



- » Compatible with EC-Oil, allowing automatic connection without the operator having to leave the cab
- » Low flow requirement (35 litres) allows the PP3200 to be run directly off the extra connections on the tiltrotator
- » Variable working width
- » Specially adapted pack cushions
- » Compaction plate in hard-wearing steel
- » Side plating for grading filler
- » Open short ends allows quick and easy clearing of the top of the plate
- » Rubber joint optimise insulation with stiffness for grading
- » The vibrator unit and hydraulic parts are well-protected inside the side plates
- » Fitted with S-type mounting as standard
- » Complies with European safety standards
- » Not supplied with hoses



Accessories

Extension plates, trenching blade, specially adapted compactor pads for e.g. packing in sheet-pilings.

The EC-Oil automatic quick hitch system is a free standard on all engcon's hydraulic tools with S40–S80 attachment

Specifications

Model	PP3200
Compaction force: (kg)	3 200
Compaction area: (m ²)	0,4–0,56
Max hydraulic pressure: (MPa)	22
Rec hydraulic flow: (l/min)	34
Max continuous return hose pressure: (MPa)	1
Weight excluding attachment point: (kg)	470
Length: (mm)	1 000
Width: (mm)	500–700
Height: (mm)	590

CHANGE THE WORLD OF DIGGING

engcon Australia | Unit 2, 18 Peter Brock Drive, Eastern Creek, NSW 2766
Tel +61 2 7252 5279 | **E-mail** australia@engcon.com | **Web** engcon.com